



# Two ventilators in one – a smart choice

## Philips Respironics V680 Ventilator

### Patient Types

Adult:	>20 kg
Pediatric:	5 to 20 kg

### Settings

Single-limb Settings	Range
CPAP	4 to 25 cmH <sub>2</sub> O
EPAP	4 to 25 cmH <sub>2</sub> O
IPAP	4 to 40 cmH <sub>2</sub> O
I-time (inspiratory time)	0.30 to 3.00 secs
Ramp time	OFF, 5 to 45 min
Rate (respiratory rate)	4 to 80 BPM
Rise (rise time)	1 to 5
Triggering and cycling	Auto-adaptive (Auto-Trak+)
O <sub>2</sub> (oxygen percent)	21 to 100%
Apnea Mode (available in CPAP mode)	Allows apnea mode settings independent of primary mode
*C-Flex	OFF, 1 to 3
*Max ΔP/min (AVAPS Max P change/min)	1.0 to 5.0 cmH <sub>2</sub> O/min
*Max P (AVAPS max IPAP)	6 to 40 cmH <sub>2</sub> O
*Min P (AVAPS min IPAP)	5 to 30 cmH <sub>2</sub> O
*VT (AVAPS target tidal volume)	50 to 2,000 ml BTPS
*Max E	0 to 100 cmH <sub>2</sub> O/l
*Max R	0 to 50 cmH <sub>2</sub> O/l/s
*PPV%	0 to 100%
*Max P (PPV max pressure limit)	5 to 40 cmH <sub>2</sub> O
*Max V (PPV max volume limit)	200 to 3,500 ml

\*Optional

### Settings (continued)

Dual-limb Settings	Range
VT (tidal volume in VCV and PRVC modes)	50 to 2,000 ml BTPS
Rate (respiratory rate)	1 to 80 BPM
I-time (inspiratory time)	0.30 to 5.00secs
Rise (rise time)	1 to 5
I-Trig (flow trigger)	0.5 to 20L/min, OFF
E-Cycle (% of peak flow)	10 to 80%
Flow Pattern	Square, Decelerating Ramp
PC (pressure control target above PEEP)	1 to 65 cmH <sub>2</sub> O
PS (pressure above PEEP)	Off, 2 to 65 cmH <sub>2</sub> O
PEEP (end expiratory pressure)	0 to 40 cmH <sub>2</sub> O
Sigh (1.5 times tidal volume)	On, Off
O <sub>2</sub> (oxygen percent)	21 to 100%
Max P (PRVC maximum pressure limit)	3 to 65 cmH <sub>2</sub> O
Max V (PRVC maximum volume limit)	50 to 2,500 ml
Min P (PRVC minimum pressure limit)	2 to 64 cmH <sub>2</sub> O
Apnea Mode (available in PSV and SIMV modes)	Allows apnea mode settings

### Modes

#### Single-limb Circuit

CPAP (continuous positive airway pressure)
S/T (spontaneous with timed backup)
PCV (pressure control ventilation)
Apnea mode (available in CPAP)
*AVAPS+ (average volume assured pressure support)
*PPV (proportional pressure ventilation)

# PHILIPS

## Modes *(continued)*

Dual-limb Circuit
A/C-VCV (assist/control-volume control ventilation)
A/C-PCV (assist/control-pressure control ventilation)
SIMV-VCV (synchronized intermittent mandatory ventilation-volume control ventilation)
SIMV-PCV (synchronized intermittent mandatory ventilation-pressure control ventilation)
PSV (pressure support ventilation)
PRVC (pressure regulated volume control)
Apnea mode (available in SIMV and PSV)

## Monitored Parameters

Patient Data	Range
O <sub>2</sub> % (measured oxygen percent)	18 to 100%
PIP (peak inspiratory pressure)	0 to 74 cmH <sub>2</sub> O
PEEP (positive end-expiratory pressure)	0 to 50 cmH <sub>2</sub> O
EPAP (expiratory positive airway pressure)	0 to 50 cmH <sub>2</sub> O
MAP (mean airway pressure)	0 to 65 cmH <sub>2</sub> O
Breath phase/trigger indicator	Spont, Support, Mand, Assist, Exhale
Ti/Ttot	0 to 99%
I:E (inspiratory to expiratory ratio)	9.9:1 to 1:9.9, and 1 to 99
Pt. trig (Patient trigger %)	0 to 100%
Te (expiratory time)	0.3 to 100 sec
Rate (total respiratory rate)	0 to 99 BPM
Spont R (spontaneous respiratory rate)	0 to 99 BPM
VE (total minute volume)	0 to 99L/min BTPS
Mand VE (mandatory minute volume)	0 to 99L/min BTPS
Spont VE (spontaneous minute volume)	0 to 99L/min BTPS
VTI (inspired tidal volume)	0 to 3,500 ml BTPS
VTE (exhaled tidal volume)	0 to 3,500 ml BTPS
Spont VTE (spontaneous tidal volume)	0 to 3,500 ml BTPS
Dyn C (dynamic compliance)	1 to 200 mL/cmH <sub>2</sub> O
Dyn Ri (dynamic resistance, inspiratory)	1 to 200 cmH <sub>2</sub> O/L/s
Dyn Re (dynamic resistance, expiratory)	1 to 200 cmH <sub>2</sub> O/L/s
Dyn E (dynamic elastance)	5 to 1,000 cmH <sub>2</sub> O/L
Dyn Pplat (dynamic plateau pressure)	0 to 70 cmH <sub>2</sub> O
F/VT (rapid shallow breathing index)	0 to 999
Pt. Leak ("unintentional" leak)	0 to 200L/min BTPS
Tot. Leak (total leak)	0 to 200L/min BTPS

## Waveforms Window

Pressure waveform	0 to 70 cmH <sub>2</sub> O
Flow waveform	-240 to 240L/min BTPS
Volume waveform	50 to 3,500 ml BTPS
F/V (flow/volume) Loop	
Flow:	+/-10 to +/-240L/min
Volume:	50 to 3,500 ml
P/V (pressure/volume) Loop	
Pressure:	Above zero: 10 to 80 cmH <sub>2</sub> O Below zero: 0 to -15 cmH <sub>2</sub> O
Volume:	50 to 3,500 ml

## Alarm Settings

Alarm	Range
Hi Rate (high respiratory rate)	5 to 90 BPM
Lo Rate (low respiratory rate)	Off, 1 to 89 BPM
Hi VT (high tidal volume)	50 to 3,500 ml
Lo VT (low tidal volume)	OFF, 5 to 1,500 ml
Hi Spont VT (high spontaneous tidal volume)	50 to 3,500 ml
Lo Spont VT (low spontaneous tidal volume)	OFF, 5 to 1,500 ml
Hi Mand VT (high mandatory tidal volume)	50 to 3,500 ml
Lo Mand VT (low mandatory tidal volume)	OFF, 5 to 1,500 ml
HIP (high inspiratory pressure)	5 to 70 cmH <sub>2</sub> O
LIP (low inspiratory pressure)	OFF, 1 to 60 cmH <sub>2</sub> O
LIP T (low pressure delay time)	5 to 60 secs
Hi Leak	OFF, 1 to 99 L/min
Low Leak (single-limb)	Automatic
Hi PEEP (pressure above set PEEP)	1 to 15 cmH <sub>2</sub> O
Hi VE (high minute volume)	OFF, 0.2 to 99l/min
Lo VE (low minute volume)	OFF, 0.1 to 98.9l/min
O <sub>2</sub> % measured (auto set (+/-6% of O <sub>2</sub> setting))	ON, OFF
Apnea T (apnea interval time)	OFF, 1 to 60 sec

All dual-limb volume measurements and volume targets are circuit compliance compensated.

## Other Settings

Setting	Range
Loudness (alarm volume)	1 to 10
Auto-volume escalation	ON, OFF
Brightness	1 to 5 relative scale
Exhalation port selection	DEP, Whisper Swivel, PEV, Other, None
Leak character selection	1, 2, 3, 4, Other
Screen lock	ON, OFF

## Other Features

### Lung Mechanics Maneuvers

Static C&R	
Static C:	1 to 200 mL/cmH <sub>2</sub> O
Static E:	5 to 1,000 cmH <sub>2</sub> O/L
Static R:	1 to 200 cmH <sub>2</sub> O/L/s
Static Pplat:	0 to 70 cmH <sub>2</sub> O
P0.1 (P100)	0 to -50 cmH <sub>2</sub> O
MIP (Maximal Inspiratory Pressure)	0 to -50 cmH <sub>2</sub> O


## Environmental

Temperature	
Operating conditions	5 to 40°C (41 to 104°F)
Storage conditions	-20 to 50°C (-4 to 122°F)
Humidity	
Operating conditions	15 to 95% (non-condensing)
Storage conditions	10 to 95% (non-condensing)
Barometric pressure	
600 to 765 mmHg [approximately -51 to 1,951 m (-167 to 6400 ft) relative to sea level]	
Dimensions	



Weight (with battery installed)	27 lb (12.3kg)
---------------------------------	----------------

Electrical	
AC voltage	100 to 240 VAC
AC frequency	50 to 60 Hz
AC power	300 VA
Battery (lithium-ion)	
Maximum system current draw:	11 A
Charge voltage:	+16.9 V maximum
Minimum operating time:	240 minutes under nominal conditions
Pneumatics	
High-pressure oxygen supply	2.76 to 6.00 bar / 276 to 600 kPa / 40 to 87 psig Flow: 175 SLPM
Air Supply	Integrated centrifugal-flow compressor
Exhalation cartridge (eSYS)	
Flow sensor:	Exhaled gas flow accuracy: +/- (0.1 SLPM +5% of reading)
Diaphragm/seat area:	6.6 cm <sup>2</sup>
Diaphragm/seat diameter:	29 mm
Oxygen sensor	
Accuracy	+/- 5% (calibrated)
T90 response	50 sec for V <sub>t</sub> = 50 ml, 21 sec for V <sub>t</sub> = 1,000 ml



© 2014 Koninklijke Philips N.V. All rights are reserved.  
Philips Healthcare is part of Royal Philips

Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Printed in The Netherlands.  
4522 991 00641 \* FEB 2014

**How to reach us**  
[www.philips.com/healthcare](http://www.philips.com/healthcare)  
[healthcare@philips.com](mailto:healthcare@philips.com)

**Product information**  
[www.philips.com/v680](http://www.philips.com/v680)